



UFO High Bay Series GL-HB01-xxxW50K-x

Technical Data

SKU: -B = BLACK FINISH -W = WHITE FINISH	GL-HB01-100W50K-B GL-HB01-100W50K-W	GL-HB01-150W50K-B GL-HB01-150W50K-W	GL-HB01-200W50K-B GL-HB01-200W50K-W	GL-HB01-250W50K-B GL-HB01-250W50K-W
Wattage	100	150	200	250
Input Voltage (VAC)	120-277	120-277	120-277	120-277
Lumens	15,000	22,500	30,000	37,500
Efficacy	150	150	150	150
CRI	71.5	71.5	71.5	71.5
L70 (Life to 70% initial output)	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours
Color Temperature (CCT)	5000k	5000k	5000k	5000k
Dimming	0-10V	0-10V	0-10V	0-10V
IP Rating	IP65	IP65	IP65	IP65
Beam Spread (Degrees)	120	120	120	120
Power Factor	0.96	0.94	0.91	0.95
THD (%)	7.75	13.9	19.14	12.47
Operating Temperature (°F)	-40 – 122	-40 – 122	-40 – 122	-40 – 122
Housing Material	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum
Diffuser Color	Clear	Clear	Clear	Clear
Mounting Options	Hook/Bracket	Hook/Bracket	Hook/Bracket	Hook/Bracket
Dimensions (Diameter x Height - Inches)	9.4x6.8	11x7.5	11x7.5	11x7.5
Weight (Lbs)	6	8.7	9.9	11.5
Warranty	5 Years	5 Years	5 Years	5 Years
Replaces	250W HID	400W HID	600W HID	1000W HID
Certifications	DLC Premium, UL, CE, FCC, RoHS, TUV ISO9001	DLC Premium, UL, CE, FCC, RoHS, TUV ISO9001	DLC Premium, UL, CE, FCC, RoHS, TUV ISO9001	DLC Premium, UL, CE, FCC, RoHS, TUV ISO9001

[Click Here To View DLC Listings Online \(Opens in a new tab/window\)](#)



UFO High Bay Series GL-HB01-xxxW50K-x

High Output

150 Lumen Per Watt Efficacy delivers powerful light output with minimum consumption. This series is powerful enough to replace HID fixtures up to 1000 watts.

Excellent Heat Management

The **die cast aluminum housing** is designed to allow air to pass through the spaces around the driver and LED array with ease effectively making the entire body of the fixture a heat sink. The ability of this design to effectively dissipate heat contributes to the maintenance free long life.

Easy Installation

Use the included eye hook to suspend this fixture or optional bracket for fixed position mounting on ceilings, walls, or floors. The included cord and plug can be removed where hardwiring is necessary. Additional leads for 0-10V dimming require no configuration if dimming is not used.

Dimming and Controls

The **0-10V dimming** compatibility allows for easy addition control devices such as motion and occupancy sensors.

Certified Quality

These fixtures are **DLC Premium** certified qualifying and the L70 50,000 hour long life is backed up by a **5 Year Warranty**.

